

Product information

AVOL STREICHERT f_6417-M



Description:

Semisynthetic Dexron III automatic transmission oil of the latest generation. For automatic transmissions, manual shift transmission, steering systems, hydraulic and lateral drives both in the car and in the commercial vehicle sector. Ensures exact friction behavior and guarantees outstanding ageing resistance. Secures the functional performance of the aggregate and ensures long service life.

Approvals and specifications:

GM DEXRON III G (GM 6417-M), III H
Ford ESP-M2C 166-H
Ford MERCON
MB 236.1, MB 236.6
Allison C4
Caterpillar TO-2
MAN 339 L1, 339 V1, 339 Z1
VOITH G607 (55.6335)
Volvo 97341
ZF TE-ML 02F/03D/04D/09/11A/11B/14A/14B/17C



Technical data:

Density at 20°C	0.842 g/ml EN ISO 3675
Viscosity at 40°C	33.8 mm ² /s EN ISO 3104
Viscosity at 100°C	7.3 mm ² /s EN ISO 3104
Viscosity index	189 ISO 2909
Pour point	-46°C ISO 3016
Flash point	205°C EN ISO 2592
Viscosity at -40°C (Brookfield)	<= 20000 mPas ASTM D 2983

Our information is based on thorough research and may be considered reliable, although not legally binding.