

Product information

AVOL STREICHERT f_multi AGX



Description:

Low-viscosity fully synthetic automatic transmission oil with high-performance additives. For automatic transmissions that are installed in various BMW, Honda, Jaguar, Land Rover, MB, Porsche, Toyota, etc. vehicles. Extremely high viscosity index guarantees excellent ageing and oxidation stability, optimal shifting under all operating conditions.

Approvals and specifications:

Aisin Warner AW-1, JWS 3324
JASO 1A, 1A-LV
ZF M-1375.4, M-1375.5, M-1375.6
BMW ATF 3+, BMW L12108
BMW 83 22 0 142 516, 83 22 0 397 114
BMW 83 22 2 152 426, 83 22 2 289 720
Fiat 9.55550-AV5
Ford MERCON SP, LV, ULV
GM DEXRON VI, HP ATF, ULV ATF
Honda ATF Z-1, DW-1 (ausgenommen CVT)
Jaguar Öl 8432, 02JDE 26444
Land Rover TYK500050, LR0022460
Land Rover LR023288, LR023289
MB 236.12, MB 236.14, MB 236.41
MB 236.15 (ausgenommen FE Vorteile)
Toyota WS, JWS 3324, NWS 9638, T-IV
VW G 055 005 A1/A2/A6, G 055 162 A1/A2/A6, G 060 162 A1/A2/A6
ZF S671 090 255, S671 090 312, AA01.500.001



Technical data:

Density at 20°C	0.843 g/ml EN ISO 3675
Viscosity at 40°C	29.8 mm ² /s EN ISO 3104
Viscosity at 100°C	6.2 mm ² /s EN ISO 3104
Viscosity index	164 ISO 2909
Pour point	-46°C ISO 3016
Flash point	217°C EN ISO 2592
Viscosity at -40°C (Brookfield)	<= 10000 mPas ASTM D 2983

Our information is based on thorough research and may be considered reliable, although not legally binding.