

Product information

AVOL STREICHERT FRACHT_G74 15W-40



Description:

AVOL FRACHT_G74 15W-40 is designed to meet the requirements of today's modern four-stroke engines, formulated to provide reliable protection for trucks and buses which run on compressed natural gas (CNG), liquefied natural gas (LNG) or liquefied petroleum gas (LPG). AVOL FRACHT_G74 15W-40 uses high-quality base oils and an advanced additive system with low-sulphated ash which delivers exceptional thermal and oxidative stability as well as nitration resistance.

Specifications and approvals //or// AVOL STREICHERT recommends this product for vehicles with the following specifications:

API CF-4
Cummins CES 20074
Detroit Diesel 93K216
MB 226.9



Technical data:

SAE class (engine oils)	15W-40 SAE J300
Density at 20°C	0.866 g/ml EN ISO 3675
Viscosity at 40°C	102.5 mm ² /s EN ISO 3104
Viscosity at 100°C	15.1 mm ² /s EN ISO 3104
Viscosity index	155 ISO 2909
Pour point	-36°C ISO 3016
Flash point	231°C EN ISO 2592
Total base number	5.1 mg KOH/g ASTM D 2896
Sulfate ash	0.5 g/100g EN ISO 3987

Our information is based on thorough research and may be considered reliable, although not legally binding.