

Product information AVOL STREICHERT s_PRIMA 0W-20



Description:


Fully synthetic low-friction premium motor oil. Guarantees maximum performance with low fuel consumption. Ensures optimum lubrication, outstanding lubricating film stability and minimum wear and deposits even under extreme loads.

Specifications and approvals //or// AVOL STREICHERT recommends this product for vehicles with the following specifications:

ACEA C5-16
API SN Plus + RC
ILSAC GF-5
BMW Longlife-14 FE+
BMW Longlife-17 FE+
Chrysler MS-12145
Chrysler MS-13340
Fiat 9.55535-GSX/DSX
Ford WSS-M2C952-A1
Ford WSS-M12R536-A

GM dexosD
MB 229.71
Opel OV0401547
Porsche C20
PSA B71 2010
Renault RN17 FE
STJLR.03.5006
STJLR.51.5122
Volvo VCC RBS0-2AE
VW 508.00/509.00

4 6 8 10



Rußansatz
Soot Thickening Reduction
Kraftstoffeinsparung
Fuel Economy
Oxidationsbeständigkeit
Oxidative Thickening Reduction
Zylinderkopfrückstand
Piston Deposits Reduction
Schlammablagerung-Tragefähigkeit
Sludge Reduction
Verschleißschutz
Wear Resistance

□ SAE 0W-20 Leichtlauf-Motorenöl
■ AVOL s_PRIMA 0W-20

Technical data:

SAE class (engine oils)
Density at 20°C
Viscosity at 40°C
Viscosity at 100°C
Viscosity index
Pour point
Flash point
Total base number
Sulfate ash

0W-20 SAE J300
0.842 g/ml EN ISO 3675
45.5 mm²/s EN ISO 3104
8.9 mm²/s EN ISO 3104
180 ISO 2909
-51°C ISO 3016
227°C EN ISO 2592
7.5 mg KOH/g ASTM D 2896
0.8 g/100g EN ISO 3987

Our information is based on thorough research and may be considered reliable, although not legally binding.